

AIREDALE

air conditioning for every environment

Convectors, Steam and Hot Water

1,000 - 27,000 BTU/h

1.000-27.000 BTU/h



> **Convectors
Steam and Hot Water**


Airedale convectors provide maximum installation flexibility for a variety of heating applications. They come in a variety of models, allowing convectors to be partially recessed, wall hung, and free standing. The heating elements can be used for hot water or steam. The standard header is copper with top and bottom tappings. Tubes are mechanically expanded into aluminum fins to form a durable bond for maximum heat transfer.

Airedale offers convectors in 20 - 64 inch lengths and 5 different heights, ranging from 14 - 32 inches depending on model. A variety of colors is offered to match any application. A complete line of options and accessories provides flexibility in design and installation.


www.airedaleusa.com

Convectors, Steam and Hot Water

1,000 - 27,000 BTU/h




Model SL
Slope-Top Wall Mounted




Model FL
Flat-Top Floor Mounted




Model SF
Slope-Top Floor Mounted



Model PL
Fully-Recessed Wall Mounted



Model WL
Flat-Top Wall Mounted



Model RL
Semi-Recessed Wall Mounted

Standard Features

- > Standard 20 Gauge Liner, 18 Gauge Front
- > Cabinets Braced and Reinforced
- > Pre-Treated for Corrosion and Finished with a Polyester-Epoxy Powder Coating
- > Heating Elements Available in Three Nominal Depths: 4" (2-tube element), 6" (3-tube element), or 8" (4-tube element)
- > Element Supported in Enclosure by a Welded Bracket to Eliminate Strain on Piping or Element
- > Fins of .010" Aluminum with Integral Collars for Uniform Spacing
- > Tubes Mechanically Expanded into Collars for Maximum Heat Transfer
- > Cast Brass Headers with Top or Bottom Tappings

Options/Accessories

- > Louvered, Security Perforated or Aluminum Bar Grille Inlet/Outlet Front Covers
- > 18, 16, or 14 Gauge Liner and/or Cover Options
- > Access Doors
- > Tamperproof Hardware
- > Insulation, 1/2" Thick Fiberglass
- > Right and/or Left Hand End Pockets
- > Optional Colors per AIR13-416
- > Outlet Damper Assembly, Knob or Tamperproof Operator
- > Reversed Header Connections
- > Wall Gasket Seal



Commercial HVAC&R Division
Modine Manufacturing Company

1500 DeKoven Avenue
Racine, WI 53403-2552

Phone : 1.866.823.1631 (toll free)
Fax : 1.800.204.6011

www.airedaleusa.com

© Modine Manufacturing Company 2005
C12/05 - 3M Litho in USA
AIR13-105